

ARTICOL: CP1 – CP2 **CODE:** 4CPV01 – 4CPV02

DESCRIPTION

CLOP is the unconventional chair for creative thinking that focuses on a new ergonomics that smoothly accommodates the way people are and do. Its dynamic personality also lends itself to new coworking and startup contexts.

SEAT/ARMRESTS: made of flexible flame-retardant polyurethane cold-molded density 70 kg/m3, in Italian Class 1, completely expanded with water and free of chlorofluorocarbons (CFC free) and hydrochlorofluorocarbons (HCFC free) with a supporting structure in steel and structural hinges in die-cast aluminum.

STRUCTURE: cradle-like steel frame with 4 conical legs screwed into high-strength steel tube \emptyset 25 to \emptyset 18 mm with nylon footpads.

FINISHES: painted in Black, White, Corten colors. Galvanized in Copper, Nickel, Gold colors.

USAGE INSTRUCTIONS

Utilization of the entire seating surface. The surface of the anatomical seat must be fully occupied. Only then is correct contact with the backrest guaranteed, thus providing adequate support.

Exact adjustment of seat height. Correct seat height means: an angle of approximately 90° at the elbow when the forearm rests horizontally on the work surface. An angle of approximately 90° at the knee when the feet are fully resting on the ground.

Dynamic seating. For dynamic seating, it is necessary to frequently change one's posture, meaning to transition as often as possible from the anterior to the posterior posture and vice versa.

Office seating usage. Office seating should only be used as intended by the intended purpose, respecting normal general precautions. In case of inappropriate use (e.g., instead of a ladder, sitting on armrests, or with extreme unilateral loads), there is a risk of accidents.

MAINTENANCE AND CLEANING

Plastic Parts: For cleaning, use a detergent with a neutral soap base. Do not use aggressive detergents.

 $\begin{tabular}{ll} \textbf{Wooden Parts}: For cleaning, use a detergent with a neutral soap base. Do not use aggressive detergents. \end{tabular}$

Metal Parts: For cleaning, use specific products for metal polishing to slow down natural oxidation due to contact.



Upholstery and Padding: Any stains on the fabric upholstery can be removed either with mild neutral detergents or with specific products recommended by the manufacturer for sanitizing and waterproofing, for better preservation of the upholstery's good condition. The paddings, if they present structural issues requiring maintenance, should be handled exclusively by specialized personnel.

ASSISTANCE

Service operations, such as replacement and interventions in the gas lift area, must be carried out exclusively by specially trained personnel, and requests should be forwarded directly to LUXY as the manufacturer, via telephone or email contact provided at the bottom of the technical sheet. Maintenance and component replacements performed by unauthorized personnel will void the warranty.

WARRANTY

Our products are guaranteed for 5 (five) years and cover manufacturing defects or defects in materials not attributable to misuse of the product or improper use (overloading components, impacts, and tears). The warranty is based on normal daily work use of 8 (eight) hours with a maximum load of 110 kg. Excluded from the warranty are excessive or improper use of the product, natural wear and tear of materials (fabrics, wheels, mechanisms, and lifts), defects caused by interventions carried out outside the manufacturer's premises, defects due to humid environments or atmospheres with salt or acid presence. Our warranties reflect the manufacturing processes applied to the materials and not their intrinsic qualities.

PRODUCT INFORMATION

The materials used are recyclable. At the end of its use, do not disperse the product in the environment, but dispose of it according to the type of material. The company reserves the right to make changes to this document and to the production, even without prior notice.









