



1831



1811



1816



1812



1804



1826



1825



1832



1820

ACTON

IT

Composizione

100% poliestere ignifugo

Peso

429 g/m²

Altezza

141 cm

Resistenza alla luce

EN ISO 105 - B02 - 6

AATCC 16.3: 40 Hours - 4

Resistenza allo sfregamento

EN ISO 105 - X12

Umido 4/5

Secco 4/5

AATCC 8

Umido 5

Secco 5

Pilling

EN ISO 12945-2

ASTM D3511

INFIAMMABILITÀ

11M UNI 9175

EN1021 -1

EN1021 -2

BS 5852 CRIB 5

TB 117:2013

IMO FTP 2010 PART 8 DIN 4102 BL

NFPA 260, CLASS 1

EN

Composition

100% fire retardant polyester

Weight

429 g/m²

Width

141 cm

Light Fastness

EN ISO 105 - B02 - 6

AATCC 16.3: 40 Hours - 4

Fastness to rubbing

EN ISO 105 - X12

Wet 4/5

Dry 4/5

AATCC 8

Wet 5

Dry 5

Pilling

EN ISO 12945-2

ASTM D3511

FLAMMABILITY

11M UNI 9175

EN1021 -1

EN1021 -2

BS 5852 CRIB 5

TB 117:2013

IMO FTP 2010 PART 8 DIN 4102 BL

NFPA 260, CLASS 1

