



1454

 **LUXY.**

CATEGORIA D/
CATEGORY D


TESSUTO/
UPHOLSTERY

GORGEOUS






1499




1477




1475




1452




1490




1470




1497




1487




1485



1482




1472



1469




1461



1463




1459




1462




1467



1455



1496





DESTINAZIONI D'USO/ APPLICATIONS

Rivestimenti per imbottiti, casa,
ufficio e contract/ Offices, hotels, institutions,
domestic use

RESISTENZA ALL'ABRASIONE (CICLI MARTINDALE)/ ABRASION RESISTANCE (MARTINDALE CYCLES)

UNI EN ISO 12947-2 100.000

RESISTENZA ALLO SFREGAMENTO/ FASTNESS TO RUBBING (EN ISO 105 - X12)

Umido/ Wet 4
Secco/ Dry 4

RESISTENZA ALLA LUCE/ LIGHT FASTNESS (EN ISO 105 - B02)

5

PILLING

(EN ISO 12945-2) 5

RESISTENZA ALLA TRAZIONE/ TENSILE STRENGTH (N)

EN ISO 13934-1

Ordito/ Warp 400
Trama/ Weft 400

UNI EN ISO 13937-3

Ordito/ Warp 48
Trama/ Weft 32

MANUTENZIONE E PULIZIA/ MAINTENANCE AND CLEANING

Usare con regolarità aspirapolvere a beccuccio
liscio, senza spazzolare/ Hoover regularly and
don't brush

GORGEOUS

CARATTERISTICHE/ DESCRIPTION

100% polisolfone (PES) Trevira CS

Altezza 140 cm

Peso 450 g/m²

Possono verificarsi differenze di colore

100% polysulfone (PES) Trevira CS

Width 140 cm

Weight 450 gr/m²

Differences in color may occur

INFIAMMABILITÀ/ FLAMMABILITY

11M UNI 9175

EN 1021 - 1

EN 1021 - 2

BS 5852 CRIB 5

IMO FTP CODE 2010

DIN 4102 B1

NF P 92 503-507 M1

UNI 9177 CLASSE 1

5 ANNI DI GARANZIA/ 5 YEARS WARRANTY

REVISIONE TESSUTI 05-2021/

FABRIC REVIEW 2021-05

