


1658

 **LUXY.**


CATEGORIA D/
CATEGORY D

TESSUTO/
UPHOLSTERY


FAME
Gabriel




1699




1676




1677




1684




1667




1681




1680




1675




1670




1687




1669




1668




1673




1697




1672




1694



1661



1659



1657





DESTINAZIONI D'USO/ APPLICATIONS
Rivestimenti per imbottiti, ufficio e contract/
Offices, contract use

RESISTENZA ALL'ABRASIONE
(CICLI MARTINDALE)/ ABRASION RESISTANCE
(MARTINDALE CYCLES)

EN ISO 12947-2	200.000
ASTM D4157-07	140.000

RESISTENZA ALLO SFREGAMENTO/ FASTNESS
TO RUBBING (EN ISO 105 - X12)

Umido/ Wet	4/5
Secco/ Dry	4/5

RESISTENZA ALLA LUCE/ LIGHT FASTNESS
(EN ISO 105 - B02) 5/7 |

PILLING (EN ISO 12945-2) 4 |

MANUTENZIONE E PULIZIA/ MAINTENANCE
AND CLEANING
Lavaggio a secco P(S)/ Dry cleaning P(S)

FAME

CARATTERISTICHE/ DESCRIPTION
95% lana Nuova Zelanda
5% poliammide
Altezza 140 cm
Peso 450 g/m²
Possono verificarsi differenze di colore

95% New Zeland wool
5% poliammyde
Width 140 cm
Weight 450 g/m²
Differences in color may occur

INFIAMMABILITÀ/ FLAMMABILITY
11M UNI 9175
EN 1021 - 1
EN 1021 - 2
BS 5852 CRIB 5
TB 117:2013
AM18-NF D 60-013-(only for fabric)
BS 5852 Part 1 0,1 Cigarette and match
OENORM A3800-B1-B3825-Q1 UK
IMO MSC 307 (88) Annex 1 part 8
MED Certificate IMO
MED Certificate IMO UK
IMO MSC
BS 476 Part 7 class 1

ASSORBIMENTO ACUSTICO / ACOUSTIC ABSORPTION
UNI EN ISO 354:2003
ISO 11654
Resistenza al flusso d'aria / Air flow resistance
EN 29053
ISO 9053-1

10 ANNI DI GARANZIA/ 10 YEARS WARRANTY

**REVISIONE TESSUTI 05-2021/
FABRIC REVIEW 2021-05**

